


IAQ MECHANICAL VENTILATION REQUIREMENTS:


ZONE #	RM NAME	OCCUPANCY CATEGORY	ASHRAE 62,1-2004 REQUIREMENT	SQFT	Ρ	MINIMUM REQUIREMENT	ENHANCED 30% REQUIREMENT	DESIGN VENTILATION
AHU-1A	MONITORING LAB	COMPUTER LAB	10 CFM/P 0.06 CFM/SQFT	350	8	101 CFM	131 CFM	140 CFM
AHU-1B FCU-1	PROJECT RM	MULTI-USE ASSEMBLY	7.5 CFM/P 0.06 CFM/SQFT	350	12	111 CFM	144 CFM	150 CFM
AHU-2A	DIRECTOR OFFICE	MULTI-USE ASSEMBLY	7.5 CFM/P 0.06 CFM/SQFT	200	8	72 CFM	94 CFM	100 CFM
AHU-2B	CONFERENCE RM	MULTI-USE ASSEMBLY	7.5 CFM/P 0.06 CFM/SQFT	350	20	171 CFM	222 CFM	230 CFM

JUNE 25, 2009 DRAWING RELEASE REVISIONS TO ACCOMODATE SANYO AC & LEED

### REVISIONS:

- 1, REVISED AC SYSTEMS TO UTILIZE SANYO ECO-I VRV R410 EQUIPMENT
- 2, ADDED SOUND ATTENUATORS ON SUPPLY & RETURN TRUNKS OF ALL CONCEALED AHUS AND FCU
- 3. ADDED MERV 13 FILTERS ON RETURN REGISTERS ON ALL AHUS AND FCU.
- 4. ADDED MERV 11 PRE-FILTER ON ALL OSA INLETS.
- 5. ADDED CO2 SENSORS TO LAB & WORKSTATION ROOMS.
- 6. ADDED CO2 SENSORS w/ CO2 DEMAND CONTROLLED VENTILATION (DCV) TO FCU-1.
- 7. ADDED SF-1 FOR DIRECTORS ROOM OSA w/ CO2 DCV.
- 8. ADDED EXPOSED OVAL DUCT TO WEST PROJECT ROOM
- 9. ADDED ACCUSTICAL ATTENUATING INLET LOUVERS ON EF-3 THRU EF-6.
- 10. ADDED SOUND ATTENUATING WRAP ON EF-3 THRU EF-6.







THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.


HAWAII 5-001:033 PREPARATORY A


KAMUELA, TMK: (3) 6-5 THESE DRAWINGS ARE PROPERTY AND COPY-RIGHT OF ENGINEER CHAS CAVEDONI, THE RECIPIENT IS NOT TO COPY DUPLICATE OR DISCLOSE THE CONTENTS


DATE ISSUED: 10/17/08


DRAWN BY: CPC

SHEET NO. M1. 2 OF 6 SHEET









THIS WORK WAS PREPARED BY ME OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION.

HAKALAU IGINEERING, LLC. PO BOX 252

ENGINEER
PO BOX
HAKALAU, E

ENERGY LAB
HAWAII PREPARATORY ACADEMY
KAMUELA, HAWAII
TMK: (3) 6-5-001:033

THESE DRAWINGS ARE PROPERTY AND COPY—RIGHT OF ENGINEER CHAS CAVEDONI, THE RECIPIENT IS NOT TO COPY DUPLICATE OR DISCLOSE THE CONTENTS TO ANY PERSON OR ENTITY EXCEPT AS EXPRESSLY AUTHORIZED BY WRITTEN AGREEMENT WITH THE ENGINEER.

DATE ISSUED: 10/17/08

DRAWN BY: CPC

SHEET NO. M1.4

5 OF 6 SHEET

## GENERAL NOTES:

1. OWNER REQUIRES THE CONTRACTOR TO IMPLEMENT PRACTICES AND PROCEDURES TO MEET THE PROJECT'S ENVIRONMENTAL GOALS, WHICH INCLUDE ACHIEVING A LEED GREEN BUILDING PLATINUM RATING AND LIVING BUILDING CHALLENGE (LBC) CERTIFICATION. SPECIFIC PROJECT GOALS WHICH MAY IMPACT THIS AREA OF WORK ARE LISTED IN THE PROJECT SPÈCIFICATIONS, DIVISION 15 AS WELL AS DIVISION 1 GENERAL NOTES. THE CONTRACTOR SHALL ENSURE THAT THE REQUIREMENTS RELATED TO THESE GOALS, AS DEFINED IN THE PROJECT SPECIFICATIONS AND IN RELATED SECTIONS OF THE CONTRACT DOCUMENTS, ARE IMPLEMENTED TO THE FULLEST EXTENT. SUBSTITUTIONS OR OTHER CHANGES TO THE WORK PROPOSED BY THE CONTRACTOR OR THEIR SUBCONTRACTORS, SHALL NOT BE ALLOWED IF SUCH CHANGES COMPROMISE THE STATED LEED AND LBC CRITERIA.

#### MECHANICAL NOTES

- 1. INSTALL AND COMMISSION ALL EQUIPMENT AND HARDWARE PER MANUFACTURES RECOMMENDATIONS, CONSTRUCTION DOCUMENTS AND ALL APPLICABLE CODES.
- 2. TEST. ADJUST AND BALANCE PER ASHRAE TEST PROCEDURES TO PROVIDE INDICATED FLOW RATES.
- 3. ALL DUCT DIMENSIONS SHOW ARE INSIDE TO INSIDE DIMENSIONS.
- 4. AHU & FCU SUPPLY & RETURN TRUNKS SHALL BE 1" THICK KNAUF INSULATION DUCT BOARD w/ ECOSE TECHNOLOGY, SIZED AS INDICATED OR EQUIVALENT WITH APPROVAL OF ENGINEER.
- 5. ALL SUPPLY AND RETURN RUNOUTS SHALL BE 1" INSULATED CAL-FLEX FLEXIBLE AIR DUCT, CLASS 1 #2PMJ OR EQUIVALENT WITH APPROVAL OF ENGINEER. EXPOSED OVAL SPIRAL DUCT INTERIOR LINED SHALL BE ECO DUCT PRODUCT FABRICATED FROM GALVANIZED G60/G90 OR EQUIVALENT. PAINT TO MATCH PER ARCHITECTURAL REQUIREMENTS.
- 6. PROVIDE EACH SUPPLY, RETURN AND OUTSIDE AIR RUNOUT WITH OPPOSED BLADE VOLUME DAMPERS AT TAKE-OFF; NAILOR INDUSTRIES TYPE OBDR, SIZED AS INDICATED OR EQUIVALENT WITH APPROVAL OF ENGINEER.
- 7. ALL CEILING SUPPLY DIFFUSERS SHALL BE NAILOR INDUSTRIES TYPE RNS, SIZED AS INDICATED W/ INTEGRAL VOLUME DAMPER OR EQUIVALENT WITH APPROVAL OF ENGINEER, COORDINATE FINISH W/ ARCHITECT.
- 8. RETURN REGISTERS SHALL BE NAILOR INDUSTRIES SERIES 51EC, SIZED AS INDICATED OR EQUIVALENT WITH APPROVAL OF ENGINEER, COORDINATE FINISH W/ ARCHITECT. PROVIDE ALL RETURN REGISTERS WITH 4" MERV 13 FILTER.
- 9. ALL SIDEWALL SUPPLY DIFFUSERS SHALL BE NAILOR INDUSTRIES ALUM, DOUBLE DEFLECTION, SERIES 51-DH, SIZED AS INDICATED OR EQUIVALENT WITH APPROVAL OF ENGINEER, COORDINATE FINISH W/ ARCHITECT.
- 10. LOCATE O.S.A. INTAKE NO LESS THAN 12 FT FROM EXHAUST VENTS.
- 11. SUPPORT AHUS FROM RAFTERS W/ 3/8" THREAED ROD AND SEISMIC ISOLATION SPRINGS AND FLEXIBLE DUCT CONNECTORS. PROVIDED LATERAL SUPPORT BRACING IF SUSPENDED LENGTH IS GREATER THAN 24".
- 12. LOCATE ACCUS ON CONCRETE PADS WITH SEISMIC AND LATERAL ISOLATION SYSTEMS IN ACCORDANCE W/ SEISMIC ZONE 4.
- 13. PROVIDE A CO2 BASED DEMAND VENTILATION CONTROL SYSTEM ON EACH OSA AIR INTAKE. THE SYSTEM SHALL INCLUDE A WALL MOUNTED CO2 SENSOR w/ STAND-ALONE CONTROLLER (HONEYWELL #C7232A), AN OPPOSED BLADE VOLUME DAMPER (LLOYD INDUSTRIES #AC20) AND A PROPORTIONAL DAMPER ACTUATOR (HONEYWELL #MN7505A) OR EQUIVALENT SYSTEM WITH APPROVAL OF ENGINEER.
- 14. PROVIDE A CO2 VENTILATION SENSOR IN WORKSTATION RM AND LAB RM FOR COMFORT CONTROL AND MONITORING. THE SYSTEM SHALL INCLUDE A WALL MOUNTED CO2 SENSOR (HONEYWELL #C7232A), OR EQUIVALENT SYSTEM WITH APPROVAL OF ENGINEER.
- 15. PROVIDE ALL CONCEALED AHUS WITH COIL RETURN SIDE UV DISINFECTION FOR COIL IRRADIATION. SYSTEM SHALL BE ULTRAVATION MODEL # UMX1902T SYSTEM INSTALLED PER MANUFACTURTURE LISTED SPECIFICATIONS.
- 16. PROVIDE ALL OSA INTAKES w/ MERV 11 FILTER, SIZED AS INDICATED.
- 17. CONDENSATE DRAINS SHALL BE SCH 80 PVC PIPE AND DRAINAGE PATTERN FITTINGS W/ SOLVENT WELDED JOINTS. PROVIDE SEAL TRAP AT CONNECTION TO UNIT AND SIZE ACCORDING TO SYSTEM STATIC PRESSURE. PROVIDE CLEAN OUT AT EACH CHANGE IN DIRECTION. WRAP PIPE W/ 1/2" ARACELL AP ARMAFLEX PIPE INSULATION. DIRECT CONDENSATE TO 6" ABOVE FINISH GRADE.
- 18. WRAP ALL REFRIGERATION LINES W/ ARMACELL AP ARMAFLEX PIPE INSULATION 3/4" THICK. APPLY TWO COATS OF WB ARMFLEX FINISH ON ALL EXTERIOR LINES OR APPROVED EQUAL.
- 19. SIZE REFRIGERANT LINES IN ACCORDANCE WITH MANUFACTUER REQUIREMENTS W/ MINIMUM PIPE RUNS, CRITICAL FOR MEETING LEED REQUIREMENTS. 20. PROVIDE GRAVITY BACKDRAFT DAMPER, SS INSECT SCREEN AND WEATHER PROOF LOUVER ON ALL EXHAUST SYSTEM TERMINATIONS. SEE ARCHITECT FOR FLASHING AND HARDWARE DETAILS.
- 21. PROVIDE CONTINUOUS ACOUSTIC DAMPING INSULATION WRAP ON EF-3 THRU EF-6 HAVING A MINIMUM DENSITY OF 2 LB/SQFT; SOUND SEAL # B-20 LAG OR EQUAL APPROVED BY ENGINEER/ARCHITECT.
- 22. PROVIDE RECTANGULAR DISSIPATIVE DUCT SILENCER ON SUPPLY AND RETURN TRUINKS OF ALL CONCEALED AHUS AND FCU, SIZED AS INDICATED. SILENCER SHALL BE RUSKIN SOUND COINTROL A-36 MODEL A OR EQUAL APPROVED BY ENGINEER.
- 23. PROVIDE SS INSECT SCREEN AND WEATHER PROOF LOUVER ON ALL OSA INLET LOUVERS, SEE ARCHITECT FOR FLASHING AND HARDWARE DETAILS.
- 24. ALL JOINTS, LONGITUDINAL AND TRANSVERSE SEAMS, AND CONNECTIONS IN DUCTWORK MUST BE SECURELY SEALED USING MECHANICAL
- FASTERNERS WITH SEALS, MASTICS, GASKETS OR TAPE SYSTEMS LISTED AND LABELED IN ACCORDANCE WITH UL 181A OR UL 181B.

25. PROVIDE OWNER WITH COMPLETE OPERATION AND MAINTENANCE DOCUMENTATION IN ACCORDANCE WITH THE COMMISSIONING PLAN OF THE OWNER.

- 26. OWNER/ARCHITECT MUST APPROVE ARCHITECTURAL FINISH OF ALL EXPOSED HARDWARE INCLUDING ALL SUPPLY DIFFUSERS, RETURN GRILLES, OSA INTAKES AND EXHUAST LOUVERS.
- 27. AUX. RADIANT COOLED FCU FOR EDUCATIONAL PURPOSES ONLY; NOT PART OF BUILDING COMFORT COOLING SYSTEM.
- 28. ALL EXHAUST DUCTS SHALL BE SINGLE WALL GALVONIZED FABRICATED AND INSTALLED IN ACCORDANCE WITH THE UMC.

# COMMISSIONIN:

- THE OWNER IS PLANNING TO ACHIEVE LEADERSHIP IN ENERGY AND ENVIRONMENTAL DESIGN (LEED) CERTIFICATION FOR THIS PROJECT AND COMMISSIONING IS A PREREQUISITE FOR THIS CERTIFICATION.
- A. COMMISSIONING IS A COMPREHENSIVE AND SYSTEMATIC PROCESS TO VERIFY THAT THE BUILDING'S ENERGY RELATED SYSTEMS ARE INSTALLED, CALIBRATED AND PERFORM ACCORDING TO THE OWNER'S PROJECT REQUIREMENTS, BASIS OF DESIGN, AND CONSTRUCTION DOCUMENTS.
- B. COMMISSIONING IS A PART OF THIS PROJECT AND ALL CONTRACTORS PERFORMING WORK GOVERNED BY THIS DIVISION OF THE SPECIFICATION SHALL REFER TO SPECIFICATION SECTION 01810 FOR COMPLETE COMMISSIONING REQUIREMENTS THAT APPLY TO ALL OF THE WORK WITHIN THIS DIVISION.

#### ENERGY CALCULATION PER ASHRAE 1989 HANDBOOK

Project:	HPA En	ergy Lab October 2008			
Location	Kamuela	, Hawaii			
Zones:	Two	Program: Elite Software CHVAC			
Input Condi	tions:				
Outdoor Co 87 F db 72° F wb		Indoor Cond 77 F db 55% RH	ditions: Latitude: 19 deg	Elevation: 2,000 ft	
Zone #1 Su	mmary Load	s: Monitor o	and Project Rooms	_	
Description:		Latent BTUH	Sensible BTUH	NET BTUH	
Roof	840 sqft	0	1,580	1,580	
Walls	985 sqft	0	2,040	2,040	
Glass	335 sqft	0	10,716	10,716	
Partition	1,008 sqf	t o	907	907	
Lighting	1 W/sqft	0	2,866	2,866	
Equipment	0.5  W/sqf	t 0	1,433	1,433	
People	18	3,600	4,500	8,100	
Ventilation	360 cfm	10,463	5,146	15,609	
DrawThru Fo	n	0	447	447	
Reserve		0	3,497	3,497	
Return Duct		0	400	400	
Supply Duct		0	800	800	
Total Load		14,063	34,332	48,396	
<u>Zone Summ</u>	<u>ary Outputs</u>	• •_			
Total Supply	y Air	1,455 cfm	Conditioned Space	e 840 sqft	
· • •		360 cfm	Supply Air/Unit A	•	
Total Exhau	st Air	0 cfm	Area/Cooling Capa	11.70 011117 00	
Total Requir	ed Cooling	4 03 Tons	Cooling Cangaity Area		

Zone #2 Su	ımmary Loads:	Conference d	and Director Roon	<u>1</u>
Description:		Latent BTUH	Sensible BTUH	NET BTUH
Roof	640 sqft	0	1,340	1,340
Walls	369 sqft	0	649	649
Glass	651 sqft	0	13,821	13,821
Partition	666 sqft	0	599	599
Lighting	1 W/sqft	0	2,184	2,184
Equipment	0.5 W/sqft	0	1,092	1,092
People	16	3,200	4,000	7.200
Ventilation	320 cfm	9,656	4,222	13,878
DrawThru Fo	ın	0	447	447
Reserve		0	3,855	3,855
Return Duct		0	400	400
Supply Duct		0	800	800
Total Load		12,856	33,408	46,264


Total Required Cooling 4.03 Tons Cooling Capacity/Area 0.0048 Ton/sqft


Zone Summary Outputs: 1,455 cfm Conditioned Space Total Supply Air Supply Air/Unit Area 2.27 cfm/sqft Total Ventilation Air Area/Cooling Capacity 166 sqft/Ton Total Exhaust Air Total Required Cooling 3.86 Tons Cooling Capacity/Area 0.006 Ton/sqft

JUNE 25, 2009 DRAWING RELEASE REVISIONS TO ACCOMODATE SANYO AC

# **REVISIONS:**

1. UPDATED EQUIPMENT SCHEDULE & NOTES TO ACCOMODATE REVISIONS DESRCIBED ON SHEET M1.1.





ACCU MOUNT DETAIL



OR UNDER MY SUPERVISION AND CONSTRUCTION OF THIS PROJECT WILL BE UNDER MY OBSERVATION. SIGNATURE:

LICENSED

PROFESSIONAL

ENGINEER

No. 9507-M

THIS WORK WAS PREPARED BY ME

ENGINEERING ADEMY

**PREPARATORY** 

THESE DRAWINGS ARE PROPERTY AND COPY-RIGHT OF ENGINEER CHAS CAVEDONI, THE RECIPIENT IS NOT TO COPY DUPLICATE OR DISCLOSE THE CONTENTS TO ANY PERSON OR ENTITY EXCEPT AS EXPRESSLY AUTHORIZED BY WRITTEN AGREEMENT

DATE ISSUED: 10/17/08

WITH THE ENGINEER.

DRAWN BY: CPC

SHEET NO. 11 6 OF 6 SHEET

# EQUIPMENT SCHEDULE

TAG ID	AREA SERVED	EQUIPMENT NAME CAPACITY		ELECTRICAL COMMENTS		CONTROLS	
ACCU-1 ACCU-2	MAUKA ZONES	AIR COOLED HEAT PUMP R-410A VRV SANYO ECO-i #CHX0522	52,000 BTUH COOLING 58,000 BTUH HEATING 10% TO 100% CAPACITY CONTROL	208/230-1-60 29 MCA 4.57 Kw INPUT	37"W x 14"D x 48" H 229 LB	SANYO BACNET INTERFACE	
AHU-1A AHU-1B	MONITORING LAB & PROJECT RM	CONCEALED DUCTED UNIT SANYO ECO—i #UHX2452	25,000 BTUH COOLING 27,000 BTUH HEATING 535 CFM @ 0.38" ESP	208/230-1-60 15 MCA 0.82/0.89 RLA 157/186 W INPUT	43"W x 24"L x 13" H 71 LB	SANYO BACNET INTERFACE	
AHU-2A	CONFERENCE RM	CONCEALED DUCTED UNIT SANYO ECO—i #DHX4852	47,800 BTUH COOLING 54,600 BTUH HEATING 1,272 CFM @ 0.67" ESP	208/230-1-60 15 MCA 3.17/3.42 RLA 644/695 W COOLING INPUT 627/756 W HEATING INPUT	40"W x 25"L x 18" H 119 LB	SANYO BACNET INTERFACE	
AHU-2B	DIRECTOR RM	WALL MOUNTED UNIT SANYO ECO—i #KHX1252	12,000 BTUH COOLING 14,000 BTUH HEATING 353 CFM	208/230-1-60 15 MCA 3.17/3.42 RLA 50/56 W COOLING/HEATING INPUT	40"W x 8"D x 12" H 31 LB	SANYO BACNET INTERFACE	
EF-1 EF-2	MEN & WOMEN RESTOOMS	INLINE CABINET FAN GREENHECK #CSP-A900	600 CFM @ 0.5" 950 RPM	120-1-60 328 W	15" L x 15"H x 24"W 59 LBS 23"W x 14"H INLET, 19"W x 8"L OUTLET	INTERLOCK TO ROOM LIGHT W/ AUTO TIME DELAY OFF SWITCH IN TAMPER PROOF BOX	
EF-3 EF-4 EF-5 EF-6	WORK SHOP & LAB	INLINE CABINET FAN GREENHECK #CSP-A1750	1,600 CFM @ 0.25" 1,130 RPM	120-1-60 550 W	15" L x 15"H x 35"W 68 LBS 33"W x 13"H INLET, 28"W x 6"H OUTLET	LOCAL AUTO/ON/OFF VARIBALE SPEED CONTROL PROVIDE POINTS FOR REMOTE MONITOR AND CONTROL WRAP UNIT WITH EXTERIOR SOUND DAMPING	
EF-7	ELECTRICAL ROOM	INLINE CABINET FAN GREENHECK #CSP-A3600	3,000 CFM @ 0.5" 1,100 RPM	120-1-60 1,330 W	17" L x 15"H x 46"W 122 LBS 44"W x 15"H INLET, 40"W x 11"H OUTLET	LOCAL AUTO/ON/OFF TEMP SWITCH W/ MANUAL SPEED CONTROLLER IN TAMPER PROOF BOX 72" A.F.F.	
EF-8	JANITOR CLOSET	INLINE CABINET FAN GREENHECK #CSP-A190	120 CFM @ 0.5" 1,400 RPM	120-1-60 100 W	11" L x 11"H x 13"W 16 LBS 23"W x 14"H INLET, 19"W x 8"L OUTLET	ON/OFF WALL SWITCH IN TAMPER PROOF BOX LOCATED 72" A.F.F.	
FCU-1	PROJ ROOM AUX. COOLING	HORIZONTAL CONCEALED FAN COIL WATER COOLED 2-PIPE TRANE #UNITRANE CO6 3CH	20,100 BTU TOTAL 780 CFM @ 0.5" 4.24 GPM @ 3.3 PSI PD	120-1-60 320 W	28" L x 10"H x 37"W 100 LBS 32"W x 6"H INLET, 34"W x 6"H OUTLET 5/8" OD SWEAT CONNENCTIONS		
SF-1	DIRECTOR RM	WALL MOUNTED FAN PANASONIC #FV-08WQ1	70 CFM	120-1-60 18 W	10x10 w/ 8ø DUCT	INTERLOCK TO AHU-2B CO2 DCV w/ ON/OFF CONTROL.	