



Navigation

- System
- ⊕ Status
- ⊕ Set-up
- ⊕ Tools
- ⊕ Security
- ⊖ Advanced
 - Disable Advanced Alert
 - Port Mirroring
 - Port Trunking
 - Virtual Cable Tester
 - ⊖ Advanced Security
 - System Authentication**
 - Port-Based Authentication
 - Trusted MAC Address
 - MAC Address Lock
- ⊕ Advanced Tools
- ⊕ Traffic Management
- ⊕ VLANS
- ⊕ Spanning Tree
- ⊕ MAC

Advanced > Advanced Security > System Authentication

User Authentication Mode:

Basic Password Only ▾

RADIUS Server IP Address:

0.0.0.0

RADIUS Shared Secret:

Select a Unique secret for validation of communication between this switch and the RADIUS server.

IP Filtering is:

Disabled ▾

*Note: If you are using a RADIUS Server, please add the **RADIUS IP address (if Remote Authentication gets involved)** and **this PC IP address** into the **IP filtering table** shown below before enabling the IP filtering function. If the RADIUS IP address is not entered in this table and User Authentication Mode is "Remote Only", after enabling IP filtering, the user will lose login authentication. If this PC IP address is not entered, this PC will lose management accessibility. Also if 802.1x port-authentication function is used, please add the 802.1x Authentication server IP address in this table.*

Allowed IP Addresses: (Single IP X.X.X.X or Range X.X.X.X-X.X.X.X)
