## **AP-Plus**<sup>™</sup>

#### 802.11b Wireless Access Point





#### **Description**

The AP-Plus<sup>™</sup> is a powerful, feature-rich, two channel 802.11b compliant 11 Mbps wireless Access Point that operates on the license-free 2.4 GHz band. It comes with the YDI AP+<sup>™</sup> firmware upgrade installed which provides enhanced features¹. For indoor applications, it extends the range of a wired Ethernet network providing easy network access to both mobile users and locations that are difficult to wire. With outdoor antennas and amplifiers, long-range line-of-site links are possible.

The AP-Plus<sup>™</sup> is great for use at a WIPOP (Wireless Internet Point of Presence) to offer high-speed wireless Internet services. It can support two independent WLAN cards. By turning one radio into an 802.11b client, the AP-Plus acts as a repeater or as a bridge to another YDI AP+<sup>™</sup> enabled AP, as well as an Access Point. It is ideal for large area Wireless LAN deployment and ease of scalability.

The AP-Plus™ uses 802.1x security protocol, which provides user-based authentication and automatic key distribution in both directions. Additional features offered are SNMP, MIB II and RADIUS support.

#### AP-Plus™ Key Features

- Offers wireless LAN access in an office environment through 802.11b radios
- Dual PCMCIA card slots allow for optimal configuration flexibility with 802.11b WLAN cards
- ➤ Ideal for use with WIPOPs to offer high-speed Internet access on the 2.4 GHz license free band
- ➤ Point-to-Point Transparent Bridge application
- ➤ FCC certified for use with YDI or Agere-powered WLAN cards, amplifiers and outdoor antennas
- > Full SNMP management, and extended MIBs and traps
- Simple firewall that blocks Network Neighborhoods between wireless clients
- > Filtering by protocol and port
- ➤ Uses IEEE 802.1x for enhanced security with certificate authentication and automatic WEP key distribution. EAP-TLS based authentication via RADIUS server
- > DHCP Client/Server and NAT features
- ➤ BOOTP/DHCP forwarding
- MAC Access Control Lists
- Radio firmware uploads loads firmware during software upgrades
- > Syslog reporting
- Configuration and monitoring is accomplished remotely through an easy to use Windows-based program
- > Supports VOIP for Spectra Link cordless phones

#### AP-Plus™ Kit Includes

- ➤ AP-Plus<sup>™</sup> Access Point
- > 110/220 VAC power supply
- > Ethernet cable
- CD-ROM with Windows-based management software and documentation

Note: WLAN PC card(s) must be ordered separately.

# Ordering Information Description YDI P/N YDI AP-Plus™ 650-900001-001

1 - For a description of the features provided by the YDI AP+ firmware upgrade, please refer to the appropriate Product Specification Sheet

Specifications subject to change without notice

Rev C Nov 2003

8000 Lee Highway Falls Church, VA 22042

Tel: (703) 205-0600 Fax: (703) 205-0610

Sales: 1-888-297-9090

WWW.ydi.com
 990 Almanor Avenue
 Sunnyvale, CA 94085
 Tel: (408) 617-8150 Fax: (408) 617-8151

Sales: 1-800-664-7060

### **AP-Plus**<sup>™</sup>

#### 802.11b Wireless Access Point



#### **AP-Plus™ Additional Features**

- ➤ Base is separable from the unit for desktop or OEM applications
- Broadcast Storm protection prevents wireless networks overloads
- Multicast filters
- VPN pass-through NAT (using IPSEC, PPTP, L2TP)
- VLAN compatibility supports VLAN bridging
- Wireless Link Test: tests signal strength, noise level and ratios of link
- Support of built-in encryption: 40-bit WEP, 128-bit RC4, and WEP-Plus encryption available in the YDI or Agerepowered WLAN cards
- Future support of 802.11a/g WLAN cards with firmware upgrade
- ➤ Optional YDI-Fi firmware upgrade can be loaded to make it a Wireless IP router (Classless and RIP)²
  - 2 For a description of the features provided by the YDI-Fi firmware upgrade, please refer to the appropriate Product Specification Sheet

Two 10/100 Base-T auto-sense
Ethernet ports

**Specifications** 

Wireless Two PCMCIA card slots

Hardware

Interface

LAN

Power Supply 100-240 VAC 50/60 Hz

Power Consumption 10 watts maximum

LEDs Ethernet Link A/B Activity, Wireless
Link A/B Activity, Power

**Physical** 

Dimensions (H x W x D) 5 x 10 x 2.75 inch (127 x 259 x 70 mm)

Weight 4 lbs (1.8 kgs)


**Environmental** 

Operating Temperature

Range -20° C to +60° C (PC Card dependant)

Humidity 95% (non-condensing)

#### AP-Plus™ front view




#### AP-Plus™ rear view



#### **Typical Application**

#### AP-Plus™ in a 2 Channel Wireless Internet Point of Presence (WIPOP)



Specifications subject to change without notice

Rev C Nov 2003

8000 Lee Highway
Falls Church, VA 22042

Tel: (703) 205-0600 Fax: (703) 205-0610

Sales: 1-888-297-9090

www.ydi.com

990 Almanor Avenue Sunnyvale, CA 94085

Tel: (408) 617-8150 Fax: (408) 617-8151 Sales: 1-800-664-7060